

# Husqvarna K 970

Sturdy, reliable, light and powerful - the K 970 power cutter is ready to perform when you are. The ultimate choice when you need an all-round cutter performing in the toughest conditions, withstanding climate and fuel variations. Suitable for road works when used with the corresponding KV 970 trolley. The trolley also means you can fully concentrate on the cutting job.

- ✿ Cutting depth, **155 mm**  
max
- ✿ Blade **400 mm**  
diameter, max
- Output power **4.8 kW**

Article number :

POWER CUTTER K 970 16" | 20mm/1" - 967 34 81-01



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.

### Easy and optimal belt tensioning

The semi-automatic SmartTension minimises the risk of under- and over tensioning.

### Easy to start

The unique design of the carburetor, cylinder and digital ignition system, together with air purge and decompression valve, ensure an easy start.

- Less slurry and low water consumption
- Magnesium blade guard
- Decreased weight
- Light and powerful
- Easy to change blade guard position
- Fits multiple blade bushings
- Maintenance-free air filter
- High power with less fuel
- Reduced wear
- Blade retarder
- Maintenance-free starter

### Sturdy and reliable

Less sensitive to outdoor conditions and fuel variations, thanks to the cylinder design and muffler with integrated heat deflector.

### Long service intervals

A strong Poly-V belt combined with our maintenance-free DuraStarter™ and efficient filter-system Active Air Filtration™ ensure long service intervals.

- Less emissions and fuel consumption
- Cuts close to walls or ground
- Active Air Filtration™
- Anti-vibration system
- DuraStarter™
- EasyStart
- Poly-V belt
- Reversible cutting arm
- SmartCarb™
- Wet cutting kit

## SPECIFICATIONS

### Engine

|                              |                            |
|------------------------------|----------------------------|
| Output power                 | <b>4.8 kW</b>              |
| Cylinder displacement        | <b>93.6 cm<sup>3</sup></b> |
| Electrode gap                | <b>0.5 mm</b>              |
| Cylinders                    | <b>1</b>                   |
| Number of strokes            | <b>2-stroke engine</b>     |
| Exhaust emissions (CO2 EU V) | <b>736 g/kWh</b>           |

### Dimensions

|                     |                |
|---------------------|----------------|
| Product size length | <b>688 mm</b>  |
| Product size width  | <b>214 mm</b>  |
| Product size height | <b>481 mm</b>  |
| Weight              | <b>11.6 kg</b> |

### Vibrations

|                              |                            |
|------------------------------|----------------------------|
| Vibrations left/front handle | <b>3.5 m/s<sup>2</sup></b> |
| Vibrations right/rear handle | <b>4 m/s<sup>2</sup></b>   |

### Cutting equipment

|                       |                |
|-----------------------|----------------|
| Cutting depth, max    | <b>155 mm</b>  |
| Blade diameter, max   | <b>400 mm</b>  |
| Arbor diameter        | <b>25,4 mm</b> |
| Blade thickness, max  | <b>5 mm</b>    |
| Peripheral speed, max | <b>90 m/s</b>  |

### Sound and noise

|                                       |                  |
|---------------------------------------|------------------|
| Sound power level, guaranteed (LWA)   | <b>115 dB(A)</b> |
| Sound pressure level at operators ear | <b>104 dB(A)</b> |

### Certifications

Cert machine dir. 2006/42/EC Decl. No.

**EURO TEST  
CERTIFICATE  
SEC/10/2286**

# Husqvarna K 760 Cut-n-Break

Our Cut-n-Break method is the natural choice when you need to cut deep without overcutting at the corners. The K 760 Cut-n-Break enables you to cut as deep as 16" from one side. The two high-speed blades make a core in the saw cut, which can then easily be broken off using the accompanying breaking tool. This way you easily work your way through the material, at a very low diamond tool and maintenance cost. Delivered with twin blades and a breaking tool.

✿ Cutting depth, **400 mm**

max

✿ Blade **230 mm**

diameter, max

● Output power **3.7 kW**



Article number :

POWER CUTTER K 760 CnB 230 mm | EL35 - 967 19 57-01

## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.

### Cost-efficient cutting method

With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.

### High performing blades included

Twin blades, with a very stable core and cutting performance are delivered with the machine.

- Easy to start
- Light and powerful: 5460 K 760 Cut-n-Break II: 148062
- High power with less fuel
- Less emissions and fuel consumption
- Blade retarder
- Maintenance-free starter
- DuraStarter™
- Active Air Filtration™
- SmartCarb™

### Exceptional cutting depth

The long body and double cutting blades allow you to make cuts up to 16" deep.

### Optimized engine performance

Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.

- Wet cutting kit
- Anti-vibration system
- EasyStart
- Adjustment to openings
- Burying of cables
- Cast concrete
- Deep cutting
- Grooves
- Pipes

## SPECIFICATIONS

### Moteur

|                              |                            |
|------------------------------|----------------------------|
| Output power                 | <b>3.7 kW</b>              |
| Cylinder displacement        | <b>73.5 cm<sup>3</sup></b> |
| Electrode gap                | <b>0.5 mm</b>              |
| Cylinders                    | <b>1</b>                   |
| Number of strokes            | <b>2-stroke engine</b>     |
| Exhaust emissions (CO2 EU V) | <b>711 g/kWh</b>           |

### Dimensions

|                     |               |
|---------------------|---------------|
| Product size length | <b>798 mm</b> |
| Product size width  | <b>246 mm</b> |
| Product size height | <b>446 mm</b> |
| Weight              | <b>9.6 kg</b> |

### Vibrations

|                              |                            |
|------------------------------|----------------------------|
| Vibrations left/front handle | <b>1.9 m/s<sup>2</sup></b> |
| Vibrations right/rear handle | <b>2.8 m/s<sup>2</sup></b> |

### Équipement de coupe

|                       |               |
|-----------------------|---------------|
| Cutting depth, max    | <b>400 mm</b> |
| Blade diameter, max   | <b>230 mm</b> |
| Peripheral speed, max | <b>80 m/s</b> |

### Son et bruit

|                                       |                  |
|---------------------------------------|------------------|
| Sound power level, guaranteed (LWA)   | <b>115 dB(A)</b> |
| Sound pressure level at operators ear | <b>101 dB(A)</b> |

### Certifications

Cert machine dir. 2006/42/EC Decl. No.

**EURO TEST  
CERTIFICATE  
SEC/13/2369**